

The "NUB" Antenna

Code: ANT-OA-NUB

Product Description

- Omni Low Profile Pole Mount Wideband Antenna, coverage 698MHz 4000MHz
- Typically both used for Outdoor distribution of GSM/CDMA WIFI/3G/4G LTE/5G services.
- Low return loss, Stable performance
- Compact, light-weight and easy to install.
- Supplied with mounting bracket.
- Connector Type N Female



Electrical Specifications		
Frequency Range (MHz)	698-4000MHz	
Polarization	Vertical	
Gain (dBi)	5	
3dB Beamwidth	H: 360° E: 60°	
VSWR	≤1.5	
Input Impedance (Ω)	50	
Maximum Power (W)	100	
Lightning Protection	DC grounding	

www.outbackantennas.com.au | sales@outbackantennas.com.au |1300 762 568



Mechanical Characteristics		
Connector type	Type N Female	
Mount Type	Mast Mount	
Cable length (Meter)	3 (customizable)	
Radome material	UV-ABS	
Mount way	Pole-Holding	
Reflector material	Brass	
Dimensions (mm)	65x65x190	
Weight (g)	380	
Electrical Characteristics		
Noise Factor (dBi)	≤1.5	
Waterproof	IP66	
Operating Temperature (°C)	-30-+60°C	
Relative Humidity	Up to 95%	
ROHS Compliant	yes	

www.outbackantennas.com.au | sales@outbackantennas.com.au |1300 762 568